



## Concord Eye-Q 4363z Specifications

<b>Format</b>	Compact
<b>Image Resolution</b>	2272x1704 (4.0MP), 2048x1536 (3.1MP), 1600x1200 (2.0MP), 1280x960 (1.2MP), 640x480 (VGA)
<b>Image ratio w:h</b>	4:3
<b>Effective pixels</b>	3.87 million
<b>Sensor photo detector</b>	4.06 million
<b>Sensor size</b>	1/1.8"
<b>Sensor type</b>	CCD
<b>Colour filter array</b>	RGB
<b>Lens</b>	7.23 - 21.7mm(equivalent to 35-105mm in 35mm format) f/2.8 - f/4.7, 6 groups 6 elements, all glass with 2 aspherical elements
<b>ISO rating</b>	Auto, 100, 200, 400 (user selectable)
<b>Zoom</b>	Optical : 3 x in 11 steps Digital : 6x
<b>Focusing Range</b>	Auto Focus: 0.6m (1.96ft) to infinity      Macro: approx. 10cm (0.3ft) to 0.6m (1.96ft) at wide zoom
<b>Aperture</b>	2 steps: f/3.0 and f/6.0
<b>White Balance</b>	Auto, Sunny, Fluorescent, Tungsten
<b>Scene Selection</b>	Off, Beach/Snow, Party/Indoor, Sunset, Night Landscape Fireworks, Night Portrait, Sport
<b>Picture Effects</b>	Black & White, Solarize, Sepia
<b>Min Shutter</b>	4s
<b>Max Shutter</b>	1/2000s
<b>Flash Unit</b>	Auto, Red Eye Reduction, Fill in, Fill in Red Eye Reduction, Flash off
<b>Flash guide no.</b>	8.50
<b>Exposure compensation</b>	+/- 0, 0.3, 0.7, 1.0, 1.3, 1.7, 2.0
<b>Metering</b>	Matrix or Spot
<b>Burst Mode or Continuous Drive</b>	7 frames in 2.3 sec with 2MP resolution
<b>Movie Clips</b>	AVI format, with audio at QVGA (320x240) resolution with 30 fps Approx. 60 sec/16MB storage
<b>Tripod mount</b>	Standard 1/4" size
<b>Self-timer</b>	10 sec
<b>Storage included</b>	16MB internal
<b>Storage Capacity</b>	up to 512MB
<b>Storage Type</b>	Internal memory and SD card
<b>Compressed format</b>	JPEG (EXIF 2.2)
<b>Quality Levels</b>	~4.5:1 (Fine)      ~11:1 (Normal)      ~17:1 (Economy)
<b>Viewfinder</b>	Optical Real image zoom finder
<b>LCD</b>	1.5" TFT LCD
<b>LCD Pixels</b>	326 x 240, 78K Pixel Resolution
<b>Playback zoom</b>	2X, 4X, 6X (2272x1704 )      2X, 4X, 6X (2048x1536) 2X, 4X, 6X (1600x1200)      2X, 4X, 6X (1280x960 )      2X, 4X (640x480)
<b>Video out</b>	Yes
<b>USB</b>	Yes, USB1.1
<b>Battery</b>	2x AA batteries, can use alkaline, lithium and rechargeable NiMH type (Highly Recommended)
<b>Power Management</b>	LCD will go to standby mode after 1 min. Camera will automatically power off after 2 min. of inactivity.
<b>Weight</b>	150g (excl. batteries and memory card)
<b>Dimensions</b>	100 x 61 x 31.5 mm without protrusions
<b>PC Software Included</b>	Acrosoft PhotoImpression 2000 (for Window only) Acrosoft Photo Transfer, Drivers for Window 98/98SE Microsoft Direct X 9.0, Adobe Acrobat 5.1 Reader
<b>Accessories</b>	2xAA batteries, Video Cable, USB cable with A and mini-B connectors, Pouch, Wrist Strap CD ROM including English, German, French, Spanish, Italian, Dutch User's Guide in PDF format, camera driver and applications English, German, French, Spanish, Italian, Dutch User's Guide, English, German, French, Spanish Quick Start Guide and warranty card
<b>System Compatibility</b>	Window 98, 98SE, 2000, ME, XP and MAC OS 9.0 and higher
<b>System Requirements</b>	300MHz Pentium II processor, 128MBytes of RAM at least 360MBytes free hard disk 1024 x 768 display with 24-bit color (True Color), 4X CD-ROM drive, one free USB port
<b>Multilanguage Support</b>	English, German, French, Spanish, Italian, Dutch, Chinese, Japanese
<b>Drivers</b>	Windows USB Mass Storage Driver
<b>Certifications</b>	CE, FCC, VCCI

Specifications are subject to change without notice.